
STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION



* Epoxy grout anchor bolt in 9" (Min.) drilled holes according to Section 584 of the Standard Specification. Cost of Beams (21" Depth).

retainer and accessories are included with Precast Prestressed Concrete Deck

PLAN

WT 8x20-

Steel Wedges - Taper to ensure tight fit

throughout.

CHECKED KPC


Section A-A

TEMPORARY RETAINER AT EXPANSION JOINT

(East Abutment Only)

1" ♦ x 12" Galv. anchor

After block-outs are poured and cured the retainer angles shall be removed. Anchor bolts may be left in place.



ROUTE NO. SECTION SHEET NO. 12 COUNTY F.A.P. 685 (39BR)I 22 21 13 SHEETS FED. ROAD DIST. NO. 7 ILLINGIS FED. AID PROJECT

Contract # 68497

ANCHOR BOLTS FOR RETAINERS

GENERAL NOTES

Holes in the masonry for anchor bolts shall be drilled according to the manufacturer's recommendation after beams or girders have been erected and adjusted.

Prior to setting the bolts, the holes shall be dry and all dust and loose

particles shall be removed by the use of compressed air or vacuuming.

The anchor bofts, furnished and installed and including the epoxy grout or capsules shall not be paid for separately but shall be included in the unit bid price for Precast Prestressed Concrete Deck Beams (21" Depth).


The Contractor may use, at his option, the capsule or the adhesive cartridge type anchor rods that have been previously tested and given a prior approval by the Department. The Contractor shall install these anchor rods in pre-drilled holes according to the manufacturer's recommendations and procedures.

The capsule or the adhesive cartridge type anchor rods shall be a two part system composed of:

- 1. A threaded rod stud with nut and washer of the type specified.
- 2. A sealed glass capsule or a sealed glass adhesive cartridge containing premeasured amounts of the adhesive chemical.

Location	Туре
East Abut.	A325

ASTM F 1554 Grade 105, ASTM A 449 and AASHTO M 314 Grade 105 anchor bolts may be substituted for the anchor bolts shown above.



(at West Abutment)

SUBSTRUCTURE DETAILS ILLINOIS ROUTE 9 OVER LOST GROVE CREEK F.A.P. ROUTE 685 SECTION (39BR)I FULTON COUNTY SN 029-0052